

MAURITIAN
STANDARD

MS ISO
4427-2:2007

First edition
2008-12-06

**Plastics piping systems – Polyethylene
(PE) pipes and fittings for water supply –
Part 2:
Pipes**

ICS 23.040.20; 91.140.60; 93.025



**Mauritius Standards Bureau
Moka**

Gr 9

National foreword

This Mauritian Standard is identical with the International Standard **ISO 4427-2:2007(E)**, *Plastics piping systems – Polyethylene (PE) pipes and fittings for water supply – Part 2: Pipes*. It was adopted by the Mauritius Standards Bureau in 2007 on the recommendation of the **Building and Construction Standards Committee** and approved by the **Standards Council** on 05 November 2008. It was notified in the Government Gazette on **06 December 2008** *.

This first edition, together with MS ISO 4427-1, cancels and replaces MS ISO 4427:1996 of which it constitutes a technical revision.

For the purposes of this standard the following changes should be made:

- (i) the words 'International Standard' should be replaced by 'Mauritian Standard';
- (ii) the "decimal comma" should be replaced by "decimal point".

The following Mauritian Standards are identical to the International Standards, which are referenced in the adopted standard:

International Standards	Corresponding Mauritian Standards
ISO 4427-1	MS ISO 4427-1 , <i>Plastics piping systems – Polyethylene (PE) pipes and fittings for water supply – Part 1: General</i>
ISO 4427-5	MS ISO 4427-5 , <i>Plastics piping systems – Polyethylene (PE) pipes and fittings for water supply – Part 5: Fitness for purpose of the system</i>

* **General Notice No 2311 of 2008.**



COPYRIGHT PROTECTED DOCUMENT

© MSB 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Mauritius Standards Bureau at the address below

*Mauritius Standards Bureau
Villa Road
Moka
Mauritius*

Telephone + (230) 433 3648
Fax + (230) 433 5051/ 433 5150
E-mail msb@intnet.mu
Website http://msb.intnet.mu

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	2
3 Terms, definitions, symbols and abbreviated terms	2
4 Material	3
4.1 Compound	3
4.2 Identification compound	3
5 General characteristics	3
5.1 Appearance	3
5.2 Colour	3
5.3 Effect on water quality	3
6 Geometrical characteristics	3
6.1 Measurements	3
6.2 Mean outside diameter and out-of-roundness (ovality)	3
6.3 Wall thicknesses and their tolerances	5
6.4 Coiled pipe	10
6.5 Lengths	10
7 Mechanical characteristics	10
7.1 Conditioning	10
7.2 Requirements	10
7.3 Retest in case of failure at 80 °C	12
8 Physical characteristics	12
8.1 Conditioning	12
8.2 Requirements	12
9 Chemical characteristics of pipes in contact with chemicals	14
10 Performance requirements	14
11 Marking	14
11.1 General	14
11.2 Minimum required marking of pipes	14
Annex A (normative) Layered pipes	15
Annex B (informative) Relationship between PN, MRS, S and SDR	17
Bibliography	18

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4427-2 was prepared by Technical Committee ISO/TC 138, *Plastics pipes, fittings and valves for the transport of fluids*, Subcommittee SC 2, *Plastics pipes and fittings for water supplies*.

This first edition, together with ISO 4427-1, cancels and replaces ISO 4427:1996, of which it constitutes a technical revision.

ISO 4427 consists of the following parts, under the general title *Plastics piping systems — Polyethylene (PE) pipes and fittings for water supply*:

- *Part 1: General*
- *Part 2: Pipes*
- *Part 3: Fittings*
- *Part 5: Fitness for purpose of the system*

Introduction

ISO 4427, the system standard, specifies the requirements for a piping system and its components when made from polyethylene (PE). The piping system is intended to be used for water supply intended for human consumption, including the conveyance of raw water prior to treatment and that of water for general purposes.

In respect of potential adverse effects on the quality of water intended for human consumption caused by the products covered by ISO 4427:

- a) ISO 4427 provides no information as to whether the products may be used without restriction;
- b) existing national regulations concerning the use and/or the characteristics of these products are in force.

NOTE Guidance for assessment of conformity can be found in Bibliographical references [5] and [6].

PREVIEW

PREVIEW

Plastics piping systems — Polyethylene (PE) pipes and fittings for water supply —

Part 2: Pipes

1 Scope

This part of ISO 4427 specifies the pipes made from polyethylene (PE) intended for the conveyance of water for human consumption, including raw water prior to treatment and water for general purposes.

It also specifies the test parameters for the test methods to which it refers.

In conjunction with the other parts of ISO 4427, it is applicable to PE pipes, their joints, to joints with components of PE and to mechanical joints with components of other materials, intended to be used under the following conditions:

- a) a maximum operating pressure (MOP) up to and including 25 bar¹⁾;
- b) an operating temperature of 20 °C as the reference temperature.

NOTE 1 For applications operating at constant temperatures greater than 20 °C and up to 40 °C, see ISO 4427-1:2007, Annex A.

NOTE 2 ISO 4427 covers a range of maximum operating pressures and gives requirements concerning colours and additives. It is the responsibility of the purchaser or specifier to make the appropriate selections from these aspects, taking into account their particular requirements and any relevant national guidance or regulations and installation practices or codes.

Three types of pipe are specified:

- PE pipes (outside diameter d_n), including any identification stripes;
- PE pipes with co-extruded layers on either or both the outside and/or inside of the pipe (total outside diameter d_n), as specified in Annex A, where all layers have the same MRS rating.
- PE pipes (outside diameter d_n) having a peelable, contiguous, thermoplastics additional layer on the outside of the pipe (“coated pipe”), see Annex A.

1) 1 bar = 0,1 MPa = 10⁵ Pa; 1 MPa = 1 N/mm².